DYSSUCTION® SUCTION DEVICE S

REF 67700



REF 67717 (optional)



- Portable suction device for subglottic suction
- Suction bag with lid for hygienic and germ-reduced replacement
- Integrated gelling agent for binding secretions
- Integrated activated charcoal filter for odour reduction in device
- Digital display in the languages German, English, French, Spanish, Italian, Dutch
- Individually adjustable
  - Vacuum: -60 mbar to -300 mbar (in 10 mbar increments)
  - Suction time: 10 - 60 sec (setting in 1-second increments)
  - Interval duration: 3 - 60 min (setting in 1-minute increments)

SCOPE OF DELIVERY

DYSSUCTION® SUCTION DEVICE S **REF 67700**
1 x suction device
1 x "Bag" external container (1000 ml) **REF 67710**
1 x "Bag" external container holder **REF 67712**
1 x "OneWay" suction bag (1000 ml)
1 x disposable secretion tube with stepped connector (non-sterile)
1 x connecting tube for "OneWay" secretion container system **REF 67713**
1 x power supply unit **REF 67912**
1 x quick reference guide
1 x Instructions for Use

Optional available:
1 x "Bag" external container (1000 ml) **REF 67710**
1 x "OneWay" suction bag (1000 ml) **REF 67711**
1 x "Bag" external container holder **REF 67712**
1 x connecting tube for "OneWay" secretion container system **REF 67713**
1 x disposable container system **REF 67714**
(outer container, suction bag, holder for outer container, connecting tube, disposable suction tube with stepped connector)
10 x disposable secretion tubes **REF 100712-1**
with stepped connector (non-sterile)
1 x replacement set double filter system DFS® **REF 67716**
1 x holder variable DYSSUCTION® Suction Device S **REF 67717**

CE 0494

DYSSUCTION® SUCTION DEVICE S





DEVICE OVERVIEW		REF
①	Carrying handle	
②	Connecting tube for "OneWay" secretion container system	67713
③	Connection suction tube	
④	Disposable secretion tube with stepped connector (non-sterile) (10 Pieces)	100712-1
⑤	External container "Bag"	67710
⑥	"OneWay" suction bag (1000 ml) (1 piece)	67711
⑦	Holder external container "Bag"	67712
⑧	Control panel	
⑨	Connection for plug-in mains unit	

TECHNICAL DATA	
Vacuum	-60 mbar to -300 mbar (in 10 mbar increments)
Suction time	10 - 60 sec (in 1-second increments)
Interval duration	3 - 60 min (in 1-minute increments)
Unit suction capacity	max. 8 l/min
Dimensions device (H x W x D)	290 x 359 x 130 mm
Weight	2.2 kg
Operating time	Mains operation: permanent operation Battery operation: approx. 18 h depending on the load on the motor
Charging time	6 – 7 h with empty battery
Sound emission	35 dB (A)
Mains voltage mains unit	100 – 240 V AC primary at 50-60 HZ

ANDREAS FAHL Medizintechnik-Vertrieb GmbH • August-Horch-Str. 4a • 51149 Köln • Germany • Phone +49 (0)2203/2980-0 • Fax +49 (0)2203/2980-100 • Mail: vertrieb@fahl.de • www.fahl.com

TD_2.4.1_DASH_67700_DYSsuction_67700_03_EN